



## NS Series (Single-MPPT, Single-Phase)

GoodWe NS series inverter adopts cutting-edge technology in photovoltaic fields, designed under modern industrial concept. Inheriting all the excellent traits from GoodWe SS and DS series, the NS series is much smarter in size and weight. It makes the series convenient for transport and suitable for different installation environments. Comprehensive MPPT technology, software and hardware technology is guaranteed to maximize the life-span of these inverters.

- Up to 10 safety measurements
- DC switch
- IP65 dust-proof and water-proof
- 45°C full-load output
- Lower start-up voltage at 80V
- Wide range of MPPT voltage
- Wireless monitoring and communication
- Fanless low-noise design
- 30% lighter than similar products
- 20% Volume optimization
- Perfect for 3-panel system

Technical Data	GW1000-NS	GW1500-NS	GW2000-NS	GW2500-NS	GW3000-NS
<b>DC Input Data</b>					
Max. allowed PV Power [W]	1300	1950	2600	3250	3900
Nominal DC Power [W]	1200	1800	2300	2700	3200
Max. DC voltage [V]	450	450	450	500	500
MPPT voltage range [V]	80~400	80~400	80~400	80~450	80~450
Starting voltage [V]	80	80	80	80	80
Max. DC current [A]	10	10	10	18	18
No. of DC connectors	1	1	1	1	1
No. of MPPTs	1	1	1	1	1
DC connector	MC4/ Phoenix/ Amphenol			MC4/ Phoenix/ Amphenol	
<b>AC Output Data</b>					
Nominal AC power [W]	1000	1500	2000	2500	3000
Max. AC power [W]	1000	1500	2000	2500	3000
Max. AC current [A]	5	7.5	10	12.5	13.5
Nominal AC output	50/60Hz; 230Vac			50/60Hz; 230Vac	
AC output range	45~55Hz/55~65Hz; 180~270Vac			45~55Hz/55~65Hz; 180~270Vac	
THDi	<3%			<3%	
Power factor	0.8 leading~0.8 lagging			0.8 leading~0.8 lagging	
Grid connection	Single phase	Single phase	Single phase	Single phase	Single phase
<b>Efficiency</b>					
Max. efficiency	96.5%	97.0%	97.0%	97.5%	97.5%
Euro efficiency	>96.0%	>96.0%	>96.0%	>97.0%	>97.0%
MPPT adaptation efficiency	99.9%	99.9%	99.9%	99.9%	99.9%
<b>Protection</b>					
Residual current monitoring unit	Integrated			Integrated	
Anti-islanding protection	Integrated			Integrated	
DC switch	Integrated (optional)			Integrated (optional)	
AC over current protection	Integrated			Integrated	
Insulation monitoring	Integrated			Integrated	
<b>Certifications &amp; Standards</b>					
Grid regulation	G83/2, VDE0126-1-1, AS4777.2&.3, EN50438, ERDF-NOI-RES_13E;			G83/2, VDE0126-1-1, AS4777.2&.3, EN50438, ERDF-NOI-RES_13E;	
Safety	According to IEC62109-1&-2, AS3100			According to IEC62109-1&-2, AS3100	
EMC	EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3			EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3	
<b>General Data</b>					
Dimensions (WxHxD) [mm]	344*274.5*128			344*274.5*128	
Weight [kg]	7.5			8.5	
Mounting	Wall bracket			Wall bracket	
Ambient temperature range	-25~60°C (> 45°C derating)			-25~60°C (> 45°C derating)	
Relative humidity	0~95%			0~95%	
Max. operating altitude	4000m(> 3000m derating)			4000m(> 3000m derating)	
Protection degree	IP65			IP65	
Topology	Transformerless			Transformerless	
Night power consumption [W]	<1			<1	
Cooling	Natural convection			Natural convection	
Noise emission [dB]	<25			<25	
Display	LCD			LCD	
Communication	USB2.0; WiFi or RS485			USB2.0; WiFi or RS485	
Standard warranty [years]	5/10/15/20/25 (optional)			5/10/15/20/25 (optional)	

Color Options